

ANALYTICAL REPORT

Mr. Richard Tyler
MILBANK MANUFACTURING INC
1400 E. Havens Street
Kokomo, IN 56901-3188

09/12/2000

Job Number: 00.04650

Page 1 of 3

Enclosed are the Analytical Results for the following samples submitted to TestAmerica, Inc. Indianapolis Division for analysis:

Project Description: WASTEWATER ANALYSIS

Sample Number

Sample Description

Date Time Taken Taken

Time Date Taken Received

274466 WEEKLY SAMPLE

08/31/2000

09/01/2000

TestAmerica, Inc. certifies that the analytical results contained herein apply only to the specific samples analyzed.

TestAmerica Incorporated-Indianapolis Division is in compliance with the National Environmental Laboratory Accreditation Program (NELAP) Standards.

Reproduction of this analytical report is permitted only in its entirety.

Project Representative

SEP 2 3 2000



ANALYTICAL REPORT

Mr. Richard Tyler
MILBANK MANUFACTURING INC
1400 E. Havens Street
Kokomo, IN 56901-3188

09/12/2000

Job No.: 00.04650

Page 2 of 3

Date Received: 09/01/2000

Job Description: WASTEWATER ANALYSIS

Sample Number / Sample I.D. Sample Date/ Analyst Reporting Date & Time Analyzed Method Parameters Wet Wt. Result Flag Units Limit 08/31/2000 274466 WEEKLY SAMPLE Zinc, ICP 0.034 mg/L tyj 09/11/2000 13:40 EPA 200.7 <0.020



KEY TO ABBREVIATIONS

SEP 2 8 2000

Page 3 of 3

- Less than; when appearing in the result column, indicates analyte not detected at or above the Reporting Limit.
- Percent; To convert ppm to %, divide result by 10,000. To convert % to ppm, multiply the result by 10,000.
- Indicates the Reporting Limit is elevated due to insufficient sample volume.
- mg/L Part per million; Concentration in units of milligrams of analyte per Liter of aqueous sample.
- ug/L Part per billion; Concentration in units of micrograms of analyte per Liter of aqueous sample.
- mg/kg Part per million; Concentration in units of milligrams of analyte per kilogram of non-aqueous sample.
- ug/kg Part per billion; Concentration in units of micrograms of analyte per kilogram of non-aqueous sample.
- a Indicates the sample concentration was quantitated using a diesel fuel standard.
- b Indicates the analyte of interest was also found in the method blank.
- c Sample resembles unknown Hydrocarbon.
- dw When indicated, the result is reported on a dry weight basis. The contribution of the moisture content in the sample has been subtracted when calculating the concentration.
- d1 Indicates the analyte has elevated Reporting Limit due to high concentration.
- d2 Indicates the analyte has elevated Reporting Limit due to matrix.
- Indicates the reported concentration is estimated.
- g Indicates the sample concentration was quantitated using a gasoline standard.
- h Indicates the sample was analyzed past recommended holding time.
- i Insufficient spike concentration due to high analyte concentration in the sample.
- j Indicates the reported concentration is below the Reporting Limit.
- k Indicates the sample concentration was quantitated using a kerosene standard.
- Indicates an MS/MSD was not analyzed due to insufficient sample. An LCS / LCS Duplicate provided for precision.
- m Indicates the sample concentration was quantitated using a mineral spirits standard.
- Indicates the sample concentration was quantitated using a motor oil standard.
- p Indicates the sample was post spiked due to sample matrix.
- q Indicates MS/MSD exceeded control limits. The associated sample may exhibit similar matrix bias. All other quality control indicators are in control.
- r Indicates the sample was received past recommended holding time.
- u Indicates the sample was received improperly preserved and/or improperly contained.
- uj Indicates the result is below the Reporting Limit and is considered estimated.
- Indicates the BOD dilution water blank depletion was between 0.2 and 0.5 mg/L.

DATE: August 31th, 2000

MILBANK MANUFACTURING COMPANY

TIME	METER READING	INITIALS
7:30	39150	SLH
8:00	39300	SLH
8:30	39480	SLH
9:00	39690	SLH
9:30	39910	SLH
10:00	40120	SLH
10:30	40300	SLH
11:00	40480	SLH
11:30	40710	SLH
12:00	40900	SLH
12:30	40120	SLH
1:00	40360	SLH
1:30	41590	SLH
2:00	41800	SLH
2:30	42010	SLH
3:00	42170	SLH
3:30	42330	SLH

8/31/00 Please test for the following highlighted

Beginning the effective date of this permit and lasting until the expiration date, the permittee is authorized to discharge process wastewater, through discharge point # 2. Discharge through discharge point # 2 shall be limited and monitored by the permittee as specified below: [1]

A.

Discharge Limitations		Monitoring Requirements	
Regulated <u>Parameter</u>	Maximum for Any one Day mg/L	Monitoring <u>Frequency</u>	Sample Type
Cadmium[5]	.02	Semi-Annual	Composite[2]
Total	2.0		
Chromium[5]	2.0	Semi-Annual	Composite[2]
Copper[5]	0.60	Semi-Annual	Composite[2]
Cyanide	0.50	Semi-Annual	Grab
Lead[5]	0.10	Semi-Annual	Composite[2]
Nickel[5]	0.80	Semi-Annual	Composite[2]
Silver[5]	0.24	Semi-Annual	Composite[2]
Zinc[5]	1.25	1 X Week	Composite[2]
Oil and Grease[6]	100	Semi-Annual	Grab
TPH[6]	(Monitor and report)	Semi-Annual	Grab
pН	6-10	Daily	Grab
CBOD [4]	(Monitor and report)	1 X Month	Composite[2]
Ammonia [4]	(Monitor and report)	1 X Month	Composite[2]
COD [4]	(Monitor and report)	1 X Month	Composite[2]
TSS [4]	(Monitor and report)	1 X Month	Composite[2]
Flow	N/A	Daily [3]	
тто	2.13	Semi-Annual	Grab
Phenol	0.50	Semi-Annual	Grab
Molybdenum[5]	(Monitor and report)	1 X Month	Composite[2]

DAILY: EVERY DAY SYSTEM RUNS

IX WEEK: S DAY OF WEEK COMPOSITE IS TAKEN (USUALLY THURSDAY)

IX HONTH: TO BE TAKEN FIRST WEEK COMPOSITE IS TAKEN FOR THAT HONTH

SEMI-ANNUAL: TO BE TAKEN PIRST WEEK IN JUNE AND PIRST WEEK IN DECEMBER

PART I

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

Beginning the effective date of this permit and lasting until the expiration date, the permittee is authorized to discharge process wastewater, through discharge point # 2. Discharge through discharge point # 2 shall be limited and monitored by the permittee as specified below: 111

	Discharge Limitations				Monitoring Requirements	
	Regulated <u>Parameter</u>	Maximum for Any one Day mg/L	RESULT	DATE TAKEN	Monitoring Frequency	Sample Type
Cd	Cadmium[5]	.02			Semi-Annual	Composite[2]
Cr	Total Chromium[5]	2.0			Semi-Annual	Composite[2]
Cu	Copper[5]	0.60			Semi-Annual	Composite[2]
C.a	Cyanide	0.50			Semi-Annual	Grab
Pb	Lead[5]	0.10			Semi-Annual	Composite[2]
Ni	Nickel[5]	0.80			Semi-Annual	Composite[2]
9	Silver[5]	0.24			Semi-Annual	Composite[2]
Zn	Zinc[5]	1.25	0.034	8-31-00	1 X Week	Composite[2]
F06	Oil and Grease[6]	100		Ü	Semi-Annual	Grab
TIL+ GREASE . YOROCARBONS	TPH[6]	(Monitor and report)			Semi-Annual	Grab
	рН	6-10			Daily	Grab
	CBOD [4]	(Monitor and report)			1 X Month	Composite[2]
Nh3	Ammonia [4]	(Monitor and report)			1 X Month	Composite[2]
	COD [4]	(Monitor and report)		-	1 X Month	Composite[2]
1	TSS [4]	(Monitor and report)			1 X Menth	Com, osite[2]
	Flow	N/A			Daily [3]	
*	T10	2.1,3			Semi-Annual	Grab
	Phenol	0.50			Semi-Annual	Grab
Mo	Molybdenum[S]	(Mon-tor and repert)			1 X Month	Composite[2]

SEND TTO CERTIFICATION STATEMENT IN LIEU OF MONITORING ALONG WITH 40 CFR CATEGORICAL STATEMENT. MUST BE SENT EVERY JUNE AND DECEMBER (SEMI-ANNUAL)